



Your light fixture was partially disassembled for packing. The Upper Arm has been removed. Please follow these instruction to re-assemble.

- 1) Unscrew Canopy A and 1/2" Lock Nut B on Lower Arm
- 2) Loosen the Set Screw in the Large Coupling C of the Upper Arm
- 3) Slide Upper Arm Large Coupling over Lower Arm to postion shown
- 4) Screw Canopy A and 1/2" Lock Nut B onto end of Lower Arm
- 5) Once Upper Arm is positioned tighten Large Coupling's set screw.

<b>Unless Otherwise Specified:</b> Dimensions in Inches Tolerances: Fractional ± Angular: Mach ± Bend ± Two Place Decimal ± Three Place Decimal ±		<b>Name</b>	<b>Date</b>	<b>Primelite Mfg. Corp.</b>  <b>23/16-875</b>		
	<b>Drawn</b>	lv	11/20/15			
	<b>Checked</b>					
	<b>ENG Appr.</b>					
	<b>MFR Appr.</b>					
	<b>QA</b>					
	<b>Comments</b>			<b>Size</b>	<b>Drawing No.</b>	<b>Rev</b>
<b>Construction: Aluminum</b>	CAD Generated Drawing Do Not Manually Update			<b>A</b>	<b>0001</b>	<b>A</b>
<b>Lamp: 1- 200A</b>				<b>Scale</b>	<b>CAD File</b>	<b>Sheet 1 of 1</b>